

UNO ENGINEERING

THE ENGINEERS ENTERPRISES

HYDRAULIC CONDUCTOR CUTTER

Hand operated Hydraulic wire cutters

APPLICATIONS: The hydraulic cutter with blades made from steel alloy of high strength and hardness is used to cut conductors like ACSR, AAAC, etc. And it can be used to cut GSW earth wire, ACS earth wire and OPGW as well. All the cutters are self-contained hand-operated hydraulic cutting tool, Designed with latch type rotatable head, double-speed pumping system, safety valve and plastic case package.

For CPC-40FR release pressure by twisting and closing handle, For CPC-40A, turn pressure release knob (installed on the side of cutter)

Specifications

Model No.	Cutting Capacity (OD in mm)									Length(mm)	Weight (kg)
	GWS			Soft /Cu/Al/Steel Bar			ACSR	Steel Guy Wire	Underground Cable		
	6*7	6*12	6*19	Soft Cu Bar/Strands	Soft Al Bar/Strands	Soft Steel Bar					
CPC-20A	16	20	20	20(Bar)	16	16	21	15	18	420	3.14
CPC-40A	/	/	/	40(Strands)	40	16	38	16	40	580	5.2
CPC-40FR	/	/	/	40(Strands)	40	16	38	16	40	650	6.6

